Incredible speeds plus rock-solid reliability

Kingston's A400 solid-state drive dramatically improves the responsiveness of your existing system with incredible boot, loading and transfer times compared to mechanical hard drives. Powered by a latest-gen controller for read and write speeds of up to 500MB/s and 450MB/s¹, this SSD is 10x faster than a traditional hard drive¹ for higher performance, ultra-responsive multi-tasking and an overall faster system.

Also more reliable and durable than a hard drive, A400 is built with Flash memory. There are no moving parts, making it less likely to fail than a mechanical hard drive. It is also cooler and guieter, and its shock and vibration resistance makes it ideal for notebooks and other mobile computing devices.

A400 is available in multiple drive form factors and capacities from 120GB-1.92TB² to give you all the space you need for applications, videos, photos and other important documents. You can also replace your hard drive or a smaller SSD with a drive big enough to hold all your files.

> Fast start-up, loading and file transfers start-up, loading and file transfers a hard drive

- > Multiple capacities with space for applications or a hard drive replacement





Features/specs on reverse >>



A400 SSD

FEATURES/BENEFITS

- > 10x faster than a hard drive¹ With incredible read/write speeds, the A400 SSD will not only increase performance but can also be used to breathe new life into older systems.
- > **Rugged** A400 is shock and vibration resistant for rugged reliability when used in notebooks and other mobile computing devices.
- > Multiple capacities A400 is available in capacities of up to 1.92TB² to suit anyone's needs.
- > Ideal for desktops and notebooks A400 comes in 2.5" 7mm and M.2 form factors to fit in a wide array of systems. It is ideal for thin and light notebooks with limited space.

SPECIFICATIONS

- > Form factor 2.5" & M.2 2280
- > Interface SATA Rev. 3.0 (6Gb/s) with backwards compatibility to SATA Rev. 2.0 (3Gb/s)
- > Capacities² 120GB, 240GB, 480GB, 960GB, 1.92TB
- > Baseline performance¹

Data transfer (ATTO)

120GB — up to 500MB/s read and 320MB/s write

240GB — up to 500MB/s read and 350MB/s write

480GB — up to 500MB/s read and 450MB/s write

960GB — up to 500MB/s read and 450MB/s write

1.92TB — up to 500MB/s read and 450MB/s write

> Power consumption 0.195W idle / 0.279W avg / 0.642W (MAX) read / 1.535W (MAX) write

- > Storage temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$
- > Operating temperature 0°C~70°C
- > **Dimensions** 100.0mm x 69.9mm x 7.0mm (2.5") 80mm x 22mm x 1.35mm (M.2)
- > Weight 41g (2.5")

5.5g (128GB - M.2)

6.7g (256GB - M.2)

- > Vibration operating 2.17G peak (7-800Hz)
- > Vibration non-operating 20G peak (10-2,000Hz)
- > Life expectancy 1 million hours MTB
- > Warranty/support³ limited 3-year warranty with free technical support
- > Total Bytes Written (TBW)4

120GB — 40TB

240GB - 80TB

480GB — 160TB

960GB — 300TB

1.92TB — 600TB



KINGSZON PART NUWBERS

2.5" (Standalone)

SA400S37/120G

240C 1480G 1709\$37/950G 15040053271920G SA400537/240G

M.2 2280

SA400M8/120G SA400M8/240G

- 1. Based on "out-of-box performance" using a SATA Rev. 3.0 motherboard. Speed may vary due to host hardware, software and usage. IOMETER random 4k random read/write is based on an 8GB partition
- 2. Some of the listed capacity on a Flash storage device is used for formatting and other functions and is thus not available for data storage. As such, the actual available capacity for data storage is les than what is listed on the products. For more information, go to Kingston's Flash Memory Guide at kingston.com/flashquide.
- 3. Limited warranty based on 3 years or "Percentage Used", which can be found using the Kingston SSD. Manager (Kingston.com/SSDManager). For NVMe SSDs, a new unused product will show a Percentage Used value of 0, whereas a product that reaches its warranty limit will show a Percentage Used value of greater than or equal to one hundred (100). See Kingston.com/wa for details
- 4. Total Bytes Written (TBW) is derived from the JEDEC Client Workload (JESD219A).



