


EDIFIER®

A100

Active Speaker System

Enter the world of Phil Jones and experience his legacy with the Airpulse A100 Active Loudspeaker. Phil is known the world over for his brilliant speaker design and engineering. His lifetime of experience is evident in the sound and quality build of the A100.



Features


- Electronic crossovers and dynamic control based on DSP
- Active HiFi speakers with Hires Audio
- Proprietary horn loaded aluminium Ribbon Tweeter
- 5" Cast frame under-hung coil woofer with hard anodized Aluminum cone
- High efficiency Class-D digital power amplification
- XMOS processor and USB audio connector
- Versatile with multiple inputs and Bluetooth wireless connection
- Available in piano lacquer finish in white, red or black
- Subwoofer output interface included

Package Info

Dimension	160 x 283 x 255mm,(WxHxD),11kg
Inner Carton	478 x343 x 368 mm, (LxWxH),12.6kg (gross weight)
Master Carton	489 x 353 x 387 mm, (LxWxH),13.4kg (gross weight)
PCS/CTN	1



Available Colors



Specifications

Tweeter	: Horn Loaded Ribbon Tweeter
Mid-Woofer	: 5 inch Aluminum Cone Underhung Design Neodymium Power
Power	: L/R(Treble) : 10W + 10W L/R(Min-Range and Woofer) 40W + 40W
Amplifier System	: Digital Amplifier With Xmos Processor
Input Sensitivity	: AUX: 450±50mV ; PC: 550±50mV ; USB: 400±50mFFs Optical: 400±50mFFs ; Bluetooth: 450±50mFFs
Frequency Response	: 52Hz-40KHz
Signal-Noise Ratio	: L/R:≥90dB(A)
Input Interface	: AUX, PC, USB, Optical, Bluetooth The USB, Optical Inputs Support Up to 192KH input Sample Rate
Sub out	: 800mV Max(Changes as the master volume changes)
Treble Trimmer	: 4KHz Shelf Filter -6dB- +2.4dB
Bass Trimmer	: 95Hz Shelf Filter -6dB~+6dB
Mains Voltage	: 100-240 V AC/50-60 Hz